

PLATINUM SERIES

High Efficiency N-type TOPCon M10R
Glass to Glass Module

550 - 580 Wp


550 Wp | 560 Wp | 570 Wp | 580 Wp
INA-144THC-GGF-XXX (XXX = 550-580 Wp)




APPLICATION : RESIDENTIAL | COMMERCIAL | INDUSTRIAL | SOLAR PARK

KEY FEATURES

1. LCOE is reduced with lower BOS costs, improving the product's value proposition and ensuring a competitive ROI.
2. Two peak performance periods for the optimal utilization of bifacial generation.
3. Hassle-free installation with the ability to be mounted vertically in the East-West direction, offering improved resistance to soiling.
4. Lower internal resistance boosts module power, helping to minimize power loss.
5. Excellent PID performance guarantees limited power degradation.
6. Reliable quality ensures better sustainability even in harsh environments such as deserts, farms, and coastlines with ammonia exposure.
7. Cylindrical tabbing wire is used to minimize shading on the cell's active area.
8. A higher number of busbars makes PV modules less prone to efficiency loss and increases tolerance to microcracks.
9. Positive Power Tolerance.



LINEAR PERFORMANCE WARRANTY



12-Year Product Warranty on
Materials and Workmanship*



30-Year Warranty for
Linear Performance*

CERTIFICATIONS & STANDARDS:

IS:14286/IEC 61215, IS/IEC 61730-1, IS/IEC 61730-2, IEC 62716,
IEC 62804, IEC 60068-2-68, IEC 61853, IEC 61701, IEC TS 63342, IEC TS 63209-1

IS 14286: 2010/IEC 61215: 2005
IS/IEC 61730 (PART 1): 2004
IS/IEC 61730 (PART 2): 2004



Caution: Please read safety and installation instructions before using the product. *Warranty: Linear performance warranty for 30 years, with degradation up to 1% in 1st year and 0.4 %/year from year 2 to year 30. Please read Insolation Energy Ltd. warranty documents thoroughly.

